



OFT-10WR1

10.1" Open Frame Tablet with RK3288

- > RockChip RK3288W Cortex-A17 Quad Core 1.6GHz
- > 2GB or 4G RAM
- > 16GB or 32GB eMMC
- > PCAP Touch
- > 10/100/1000 Ethernet
- > M.2 B-Key(3042) connector socket
- > 802.11 b/g/n Wireless LAN and Bluetooth 4.0
- > DC 12~24V Input
- > Optional Powered LAN 802.3AT
- > Optional 1000 nits / PCAP Touch with 3mm CG
- > OS Image support Android 8.1 / Debian 9
- > Battery Charger
Note : You need a 19v or a 24v power adapter to fully charge the battery. You cannot fully charge the battery with a 12v power adapter.

+ Spec

System	
Processor	RockChip RK3288W Cortex-A17 Quad Core 1.6GHz
System Memory	2GB or 4GB DDR3L RAM
Storage	
Storage	16GB or 32GB eMMC
I/O	
External I/O Connector	1 x Power Jack 1 x HDMI Port 2 x USB Type A Host 1 x RJ45 1 x Headphone Jack 1 x Micro SD slot 1 x Reset
Internal I/O Connector	1 x Micro USB 1 x USB interface , 1 x DMIC interface 1 x USB touch interface 1 x M.2 B-Key(3042) 1 x touch button control(power/vol/brightness) 1 x Power interface (12~24V) 1 x Li-Battery connector 1 x JLVDS1 1 x JMIPI 1 x AMIC interface 1 x Speaker interface 1 x JSEN1 interface (I2C x2) 1 x JTP1 interface 1 x Debug port 1 x RS232 interface 1 x RS232 , RS485 1 x JGPIO1 (GPIO 16bit) 1 x RTC Battery interface 1 x Micro SIM Card socket for LTE module
Display	
Multiple Display	LVDS+HDMI
Mechanical & Environmental	
Power Requirement	DC 12~24V Input
Power Type	DC Jack, DC input 4pin header (Optional Powered LAN 802.3AT)
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C0
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Weight	1.18kg
Dimension (L x W x H)	252 x 166 x 38mm
Certifications	
Certification Information	CE, FCC Class A
Software Support	
OS Information	Android 8.1 / Debian 9
Panel	
LCD Size	10.1"



Luminance	350 nits Optional 1000 nits
Viewing angle	170° (H/V)
Touch Type	PCAP
Wireless Communication	
WLAN	802.11 b/g/n
Bluetooth	4.0

+ Ordering

OFT-10WR1-DC in
OFT-10WR1-Powered LAN