

KBox C-103-CFL-x



High-End Industrial Computer Platform for Control Cabinet Applications

- ▶ Based on 8th/9th Gen Intel® Core™ or Xeon® E-2276ME for demanding control applications
- ▶ Highest system availability: Fanless up to 75 °C, Goldcap backup, redundant PSU option, recovery button
- ▶ Optimized for control and Soft-PLC applications: Fieldbus and NVRAM option
- ▶ High flexibility and expandability

POSSIBILITIES START HERE



▶ TECHNICAL INFORMATION

| | KBox C-103-CFL-4 | KBox C-103-CFL-2 | KBox C-103-CFL-1 | KBox C-103-CFL-0 |
|---|---|---|---|---|
| PROCESSORS | 8th/9th Generation Intel® processor via COM Express® type 6: - Xeon® E-2276ME: 6x 2.8 GHz, 12 MByte cache - Core™ i7-9850HE: 6x 2.7 GHz, 9 MByte cache - Core™ i5-8400H: 4x 2.5 GHz, 8 MByte cache - Core™ i3-9100HL: 4x 1.6 GHz, 6 MByte cache - Celeron® G4930E: 2x 2.4 GHz, 2 MByte cache | | | |
| PLATFORM CONTROLLER HUB | Intel® CM246 (Xeon®) or QM370 | | | |
| MEMORY | Up to 64 GByte DDR4 RAM, non-ECC/ECC | | | |
| NON-VOLATILE RAM (NVRAM) | 1 MByte FRAM optional | | | |
| RTC | High-precision RTC with gold-cap backup | | | |
| INTERFACES | 4x 10/100/1000 MBit/s Ethernet with IEEE1588 support, WOL 3x USB 3.0, 3x USB 2.0 2x DisplayPort, optional 3rd DP or Kontron Widalink via adapter module 1x RS232/RS422/RS485, 2 nd COM port optional via adapter module CAN optional via adapter module 8x LEDs 2x Buttons: Power/Reset & Recovery | | | |
| STORAGE DRIVES | 1x M.2 Key B and 1x M.2 Key M, 2x 2.5" SATA SSD/HDD internal, optional accessible via removable drive assemblies | 1x M.2 Key B and 1x M.2 Key M, 2x 2.5" SATA SSD/HDD internal, optional accessible via removable drive assemblies | 1x M.2 Key B and 1x M.2 Key M, 1x 2.5" SATA SSD/HDD internal, optional accessible via removable drive assembly | 1x M.2 Key B and 1x M.2 Key M, 1x 2.5" SATA SSD/HDD internal |
| EXPANSIONS | 2x PCIe x4 + 2x PCIe x1, 1x mPCIe for Fieldbus or WIFI expansion 1x M.2 Key B for LTE expansion, SIM card socket | 2x PCIe x4, 1x mPCIe for Fieldbus or WIFI expansion 1x M.2 Key B for LTE expansion, SIM card socket | 1x PCIe x4, 1x mPCIe for Fieldbus or WIFI expansion 1x M.2 Key B for LTE expansion, SIM card socket | 1x mPCIe for Fieldbus or WIFI expansion 1x M.2 Key B for LTE expansion, SIM card socket |
| POWER SUPPLY | 24 VDC (17-36 VDC), up to 20 ms hold-up 2nd 24 VDC power input optional via adapter module | | | |
| DIMENSION (H X W X D) | 290 x 195 x 210 mm (11.42" x 7.68" x 8.27") | 290 x 155 x 210 mm (11.42" x 6.1" x 8.27") | 290 x 130 x 210 mm (11.42" x 5.12" x 8.27") | 290 x 117 x 210 mm (11.42" x 4.61" x 8.27") |
| MOUNTING | Control cabinet key holes, book size format | | | |
| COOLING | Fan less | | | |
| ENVIRONMENTAL OPERATING TEMPERATURE STORAGE TEMPERATURE CLIMATIC HUMIDITY | with Intel® Core™ i3/i5: 0 °C to +75 °C (32 °F to 167 °F) planned with Intel® Core™ i7/Xeon®: 0 °C to +60 °C (32 °F to 140 °F) planned -40 °C to +75 °C (-40 °F to 167 °F) 93 % RH at 40 °C, non-condensing (acc. to IEC 60068-2-78) | | | |
| APPROVALS | CE, CB, UL, FCC planned | | | |
| SOFTWARE SUPPORT | Windows® 10, Windows® Server 2019, Ubuntu Linux® | | | |
| SECURITY FEATURES | TPM 2.0 controller and Kontron APPROTECT security solution based on Wibu-Systems CodeMeter® | | | |
| WEIGHT | 6 kg (13.22 lbs.) | 4.75 kg (10.47 lbs.) | 4.6 kg (10.14 lbs.) | 3.8 kg (8.37 lbs.) |

▶ Global Headquarters

Kontron S&T AG

Lise-Meitner-Str. 3-5
 86156 Augsburg, Germany
 Tel.: + 49 821 4086 0
 Fax: + 49 821 4086 111
 info@kontron.com
www.kontron.com



HY-LINE Computer Components Vertriebs GmbH

Inselkammerstr. 10 | 82008 Unterhaching

+49 89 / 614 503 40

+49 89 / 614 503 50

computer@hy-line.de

hy-line-group.com
 LEADER IN TECHNOLOGY.

