

Brief spec.; 8.4"SVGA LED Backlight & w/ 4-wire Resistive TP model

Features

- Touch panel attached
(4-wire analog resistive)
- LED Lifetime 60,000h
- LED Unit Replaceable
- Narrow bezel &
Mechanically symmetric design
- Natural Color Matrix

TYPE NAME		AA084SB01--T2
Schedule		MP Now
Screen Size / Resolution		21.3cm (8.4-inch) / SVGA
Active Screen Area Size [mm]		170.4(H) x 127.8(V)
Pixel Number		800(H) x 600(V)
Pixel Pitch [mm]		0.213(H) x 0.213(V)
Contrast Ratio		570:1
Brightness [cd/m ²]		480 (IF=60mA)
Viewing Angle (CR>10) [°]		-80~80(H), -60~80(V)
Optimum Viewing Angle (Max. CR)		6 o'clock
Colors		262k(6bit)/16.7M(8bit)
Color Saturation (vs. NTSC) [%]		40
Natural Color Matrix		Yes
Backlight		LED (Replaceable)
Lamp/LED Life [h]		Min. 60000
Interface		LVDS
Power Consumption [W]		4.7
Power Supply [V]		3.3
Reverse Scan		Available
Module Outline Dimensions [mm]	W	199.5
	H	149
	D	13.8
Module Mass [g]		500
Operation Temperature Range [°C]		-20~70
Storage Temperature Range [°C]		-30~80
Surface Treatment		Anti-glare