

Comparison Chart

Features	CRT to LCD-5	CRT to LCD-6 "Light"	CRT to LCD-6 "Full"	CRT to LCD-7 "Light"	CRT to LCD-7 "Full"	CRT to LCD-8 "Light"	CRT to LCD-8 "Full"
Analog RGB input ("VGA")	X	X	X	X	X	X	X
DVI input	X	-	X	X	X	X	X
NTSC/PAL (CVBS)/ S-Video input	-	-	-	-	X	-	X
Analog YPbPr (Component) input	-	-	-	-	TVtoLCD	-	-
Dimensions in mm (big)	180x119,5	-	-	180x119,5	180x119,5	180x119,5	180x119,5
Dimensions in mm (small)	-	95x118,6	95x118,6	-	-	-	-
Resolution SXGA max.	X	X	X	-	-	X	X
Resolution >= UXGA	-	-	-	X	X	-	-
Frame Buffer	-	-	-	16MB	16MB	4MB	4MB
Picture in Picture	X	X	X	X	X	-	-
TTL panel output	X	X	X	X	X	-	-
LVDS panel output	X	X	X	X	X	X	X
TV tuner (optional)	-	-	-	-	X	-	-
Specials	-	-	-	Connector for light sensor to control backlight brightness		widerange power supply 12 - 24 V DC	

X = Feature available
- = Feature not available