

All SDI Converters in a 1RU 19" frame – BR-200



[Front view]



[Rear view with SDIH-100, HDMS-100 and SDIS-14]

Descriptions

OPTICIS BR-200 is 1RU 19" rack mountable frame to provide power and support various SDI converters from Opticis. It offers space for 4 converters in a 1RU, 19" rack and can be configured with any combination of 4 converters out of HDMI to SDI, SDI to HDMI, Composite or S-Video to SDI, component video to SDI, SDI to composite or S-Video and 1:5 SDI distributors. Each converter could be used in a stand-alone type too.

Key Features

- 1RU, 19" rack mountable frame
- Has space for 4 slots
- Dual fan forced-air cooling
- Offers 3 lines status LED;
 - 1st line (Green): Power on
 - 2nd line (Yellow): Input active
 - 3rd line (Red): Output active
- Dimension: 430 x 44 x 251mm (WHD)
- Power: 95~240VAC, 50-60Hz

Mountable converters

- 1. SDI-to-HDMI: SDIH-100 (1-slot taken)**
Converts multi-rate SDI to HDMI
Supports up to 3G-SDI/1080p
- 2. HDMI-to-SDI: HDMS-100 (1-slot taken)**
Converts HDMI to SDI
Supports up to 3G-SDI/1080p
- 3. 1:4 SDI Splitter: SDIS-14 (2-slot taken)**
Makes one SDI signal split into five SDI signals
Supports up to 3G-SDI/1080p
- 4. Composite or S-Video-to-HD-SDI: COMS-100 (1-slot taken)**
Converts composite or S-Video to HD-SDI
Offers up conversion feature
Provides separate audio input
- 5. Component-to-HD-SDI: COMS-200 (1-slot taken)**
Converts component video to HD-SDI
Provides separate audio input for audio
- 6. HD-SDI-to-Composite or S-Video: SDIC-100 (1-slot taken)**
Converts HD-SDI to composite or S-Video
Offers down conversion feature
Extracts audio signal from SDI

Opticis Co., Ltd.

501, Byucksan Technopia, 434-6
Sangdaewon-Dong, Chungwon-Ku,
Sungnam City, Gyeonggi-Do, 462-716
South Korea
Tel : +82 (31) 737-8033~8
Fax: +82 (31) 707-8079
www.opticis.com
tosales@opticis.com

North American Office

Opticis USA LLC
649 Route 206
Unit 9 Suite 307
Hillsborough, NJ 08844
Tel: 908-837-9652
Fax: 908-837-9078
cdkim@opticis.com