



HDMI 2.0 Detachable ACTIVE OPTICAL CABLE, HDFC-200D

Detachable HDMI 2.0 active optical cable, HDFC-200D, enables to transmit 4K (4096x2160) at 60Hz signal up to 100m (384feet) over plenum graded & LSZH hybrid cable. It avoids any scaling or data compression for lessening a burden of data transmission.

HDFC-200D is designed compact enough to be fitted into various installation environments with cutting edge technology performance.

HDFC-200D offers perfect flexibility during installation by separating HDMI connector part and Active Optical Cable part. It gives slim, light, easy installation like a general copper HDMI cable.

It can be operated by external USB power on the RX side of the cable. Optional USB power cable on TX side is available upon request.

High-Retention HDMI connector, which allows for more retention force than standard HDMI connector, prevents accidental disconnection.

HDFC-200D is compliant with HDMI standards features like CEC, EDID, and HDCP 2.2 for better installation flexibility and compatibility.

Specification

- Extends up to 4K (4096x2160) at 60Hz, (RGB & YCbCr : 4:4:4)
- Transmits HDMI 2.0 data up to 100m (328feet) over hybrid cable
- Adopts plenum graded & LSZH (Low Smoke Zero Halogen) hybrid cable
- Offers perfect flexibility during installation by separating HDMI connector from cable
- Prevents accidental disconnection by using High-Retention HDMI connector
- Supports 3D contents transmission
- Supports HDMI2.0 standards feature
- Complies with CEC, EDID, and HDCP 2.2

Applications

- Home AV
- Digital Signage
- Control room
- Conference room
- Rental staging

Vertrieb durch / Distribution by

HY-LINE[®]
COMPUTER COMPONENTS


Inselkammerstr. 10
D-82008 Unterhaching
Tel.: +49 89 614 503 40
www.hy-line.de

HDMI 2.0 Detachable ACTIVE OPTICAL CABLE, HDFC-200D

Technical Features


Resolution	Up to 4K(4096x2160) at 60Hz
Bit rate	Up to 6.0 Gbps/ch
Maximum distance	Up to 100m (328feet) @4K, 60Hz
Cable	Plenum graded & LSZH hybrid cable (optical fiber + copper cable)
Power supplying	USB power on RX side
LED Indicators	TX / RX power
Power consumption	< 1.6W
Operating temperature	0°C to 60°C
Size (LWH)	50.0 x 20.0 x 10.4 mm

Dimension [mm]



Connection Diagram

4K (4096x2160) @60Hz up to 100m



Example: PC and Display Set-up

TX: PC, laptop, or media player

RX: Monitor, TV and Projector that has USB input



Opticis Co., Ltd.

16Fl, Kins Tower 8 Sungnam-daero, 331 beon-gil, Bundang-gu
Sungnam-si, Gyunggi-do, 13558 South Korea

Tel: +82 (31) 719-8033

Fax: +82 (31) 719-8032

tosales@opticis.com



All contents are subject to be changed without prior notice.